



END USER INSTRUCTIONS - READ BEFORE USE

PRODUCT NAME:

NavBoard® Rotary™

PART NUMBER:
NB-RFM01XX

PACKAGE INCLUDES:



ADJUSTING THE TENSION HINGE



Slightly turn the tension screw one way or the other to match the required tension.

OPEN CAMERA TO VIEW USER INSTRUCTIONS OR VISIT WWW.SSPGEAR.COM/END-USER-INSTRUCTIONS





PRODUCT NAME:

NavBoard® Rotary™

PART NUMBER:
NB-RFM01XX

ATTACHING TO THE PLATEFRAME™ MODULAR (PF-M) USING MOLLE/PALS



1 Open the long Velcro straps on back panel



2 The NavBoard™ Rotary attaches to the PlateFrame™ Modular (PF-M) using the slots indicated above.



3 Insert the long Velcro straps through the slots as shown. This step can be accomplished without removing the ballistic plate. Flip the Rotary down.



4 Feed straps through bottom slots on Rotary back panel. Connect the Velcro straps to the Rotary's back panel Velcro.



5 Lift the top short Velcro straps. Place top Velcro straps down on bottom Velcro flaps and secure firmly. Repeat with second Velcro strap.



6 Close the Rotary panel and secure using the retaining strap to ensure proper fit.

ATTACHING A DEVICE TO THE ROTARY™



1 Attach adhesive-backed Velcro strip to the back of your device.



2 Place device on Rotary panel and secure it on all four corner retention bands.



3 Close the Rotary panel and secure using the retaining strap to ensure proper fit.